

Gas solenoid valves

VA.. series

The VA series of gas solenoid valves are used for safety and control of gas in gas feed pipes. They are suitable for use with various gases including Natural Gas, Propane and LPG.

These solenoid valves are normally closed (fail safe), but open automatically when the coil is powered (auto reset).

TECHNICAL INFORMATION

Power supply: 230Vac or 24Vac

Body: aluminium

Working temperature: -15°C / +60°C

Closing time: <1 sec

Max pressure: DN15 - 360mBar, DN20 up to DN100 - 200mBar

Protection level: IP54



VA.. series

Code	Connections	Flow (m3/h)	Pressure (max mBar)	Absorption (W)
VA770	DN15	6.4	360	14
VA771	DN20	14.8	200	20
VA772	DN25	16.7	200	20
VA773	DN32	38.5	200	40
VA774	DN40	47.1	200	40
VA775	DN50	66.7	200	41
VA777	DN60	94.2	200	62
VA778	DN80	131	200	118
VA779	DN100	264	200	130

Setpoint Solutions

20a Glover Street
Wellington
Phone: 04 471 2700
Fax: 04 471 2701

59b Carlyle Street
Christchurch
Phone: 03 377 5230
Fax: 03 377 5240

29 Leith Street
Dunedin
Phone: 03 477 1300
Fax: 03 477 1800